

ECONÈSOS

Ventilated refrigeration island for display ice-cream,
frozen food and fresh pre-packed product.
TB version temperature -18/-15°C
TB/TN version temperature -18/-15°C, -1/+5°C

ECONÈSOS island plug-in, exclusive design; guarantees low consumption,
wide display capacity and optimum visibility of the products.



REFRIGERATION ARCHITECTURE



- Models available: 150, 200, 250
- Upper in tempered glass
- High visibility of display products
- Internal lighting in the upper profile
- Profiles and bumpers in PVC, available in five colours
- Insulation in polyurethane at high density
- Ventilated refrigeration
- Automatic defrosting
- Automatic evaporation system of condense water
- Divider for refrigerated unit (optional)
- Night covers (optional)
- Available in three aesthetic solutions: standard, colours and fashion

RANGE OF COLOURS AVAILABLE: COLOURS AND FASHION



ECONÈSOS 200 STANDARD



ECONÈSOS 200 COLOURS

ECONÈSOS 200 FASHION

ECONÈSOS

DESIGN

ECONÈSOS is an island with an innovative design to display the product in a practical and functional way. Each element of ECONÈSOS has been designed to pay attention to aesthetics, without sacrificing the functionality.

TECHNICAL

ECONÈSOS is produced with advanced technological solutions which guarantee the finest performance and a durable life time.

EFFICIENCY

The particular technical solutions allow to combine a high display capacity with limited dimensions. ECONÈSOS is particularly suitable to the small and medium outlets. The wide personalisable spaces make ECONÈSOS an item extremely valid to sell promotional products in big outlets.


QUALITY

To us quality means flexible design, perfection in the details and total reliability over the time. Such goals can be obtained only through professionalism and passion of hundreds ISA men, continuously working to increase the levels of customers' satisfaction.

Ventilated refrigeration island for display ice-cream, frozen food and fresh pre-packed product.
TB version temperature -18/-15°C
TB/TN version temperature -18/-15°C, -1/+5°C



REFRIGERATION ARCHITECTURE



ECONÈSOS



Upper in tempered glass



Profiles and bumpers in PVC

Technical features

	150 TB; TB/TN	200 TB; TB/TN	250 TB; TB/TN
LxPxH mm	1540x1040x885	2040x1040x885	2540x1040x885
Capacity (gross/net) litres	509/235	691/399	872/504
Product temperature °C	-18/-15 ; -1/+5	-18/-15 ; -1/+5	-18/-15 ; -1/+5
Voltage v/Hz	230/50	230/50	230/50
Electrical input (standard) W/A	1050/6.1	1150/6.6	1300/7.5
Electrical input (defrosting) W/A	1600/7.2	2300/10.0	3000/13.0
Defrosting	electrical	electrical	electrical
Net weight kg	183	214	241



Sistema di Qualità
ISO 9001
Cert. CISQ/CSQ 9105, ISA 1
cisa I:Net csq
ISA S.p.A.
Via del Lavoro, 5
06083 BASTIA UMBRA (PG) ITALY
Tel. 075-80171 - Fax 075-8000900
<http://www.isaitaly.com>