

ECOPLINTOS

Static refrigeration island for display ice-cream and frozen food.
TB version temperature -18/-15°C

ECOPLINTOS island plug-in, unique in its typology for design, quality of finishing, net display capacity



REFRIGERATION ARCHITECTURE

- Models available: 150, 200, 250
- Profiles and bumpers in PVC, available in five colours
- Static refrigeration
- Automatic defrosting
- Automatic evaporation system of condense water
- Divider for refrigerated unit (optional)
- Night covers (optional)

- Available in three aesthetic solutions: standard, colours and fashion

RANGE OF COLOURS AVAILABLE: COLOURS AND FASHION



ECOPLINTOS 200 FASHION



ECOPLINTOS 200 STANDARD



ECOPLINTOS 200 COLOURS

ECOPLINTOS

DESIGN

ECOPLINTOS is an island with an innovative design to display the product in a practical and functional way. Each element of ECOPLINTOS has been designed to keep attention to aesthetics, without sacrificing the functionality.

TECHNICAL

ECOPLINTOS is produced with advanced technological solutions which guarantee the finest performance and a durable life time.

EFFICIENCY

The particular technical solutions allow to combine a high display capacity with limited dimensions. ECOPLINTOS is particularly suitable to the small and average outlets. The wide personalisable spaces make ECOPLINTOS an item extremely valid to sell promotional products in big outlets.


QUALITY

To us quality means flexible design, perfection in the details and total reliability over the time. Such goals can be obtained only through professionalism and passion of hundreds ISA men, continuously working to increase the levels of customers' satisfaction.

Static refrigeration island for display ice-cream and frozen food.
TB version with temperature -18/-15°C



REFRIGERATION ARCHITECTURE



ECOPLINTOS



Profiles and bumpers in PVC



Night covers in ABS

Technical features

	150 TB	200 TB	250 TB
LxPxH mm	1540x1040x921	2040x1040x921	2540x1040x921
Capacity (gross/net) litres	548/360	748/508	948/631
Product temperature °C	-18/-15	-18/-15	-18/-15
Voltage v/Hz	230/50	230/50	230/50
Electrical input (standard) W/A	1000/5.6	1100/5.8	1400/7.7
Electrical input (defrosting) W/A	1400/6.4	1700/7.7	2200/9.8
Defrosting	electrical	electrical	electrical
Net weight kg	160	174	197



ISA S.p.A.
Via del Lavoro, 5
06083 BASTIA UMBRA (PG) ITALY
Tel. 075-80171 - Fax 075-8000900
<http://www.isaitaly.com>