

NÈSOS

Ventilated refrigeration island for display ice-cream,
frozen food and fresh pre-packed products.
TB version temperature -18/-15°C
TB/TN version temperature -18/-15°C, -1/+5°C

NÈSOS island plug-in, exclusive design; guarantees low consumption,
wide display capacity and optimum visibility of the products.



REFRIGERATION ARCHITECTURE



- Models available: 150, 200, 250, 150 TP, 200 TP
- Profiles and bumpers in PVC, available in five colours
- Ventilated refrigeration
- Automatic defrosting
- Automatic evaporation system of condense water
- Self rolling curtain internal between two upper slanting profiles (optional)
- Divider for refrigerated unit (optional)
- Night covers (optional)

- Available in three aesthetic solutions: standard, colours and fashion

RANGE OF COLOURS AVAILABLE: COLOURS AND FASHION



NÈSOS 200 STANDARD



NÈSOS 200 COLOURS

NÈSOS 200 FASHION

NÈSOS

DESIGN

NÈSOS is an island with an innovative design to display the product in a practical and functional way. Each part of NÈSOS has been designed to pay attention to aesthetics, without sacrificing the functionality.

TECHNICAL

NÈSOS is produced with advanced technological solutions which guarantee finest performance and a durable life time.

EFFICIENCY

The particular technical solutions allow to combine the high display capacity with limited dimensions. NÈSOS is particularly suitable to the small and medium outlets. The wide personalisable spaces make NÈSOS an item extremely valid to sell promotional products in big outlets.


QUALITY

To us quality means flexible design, perfection in the details and total reliability over the time. Such goals can be obtained only through professionalism and passion of hundreds ISA men, continuously working to increase the levels of customers' satisfaction.


Ventilated refrigeration island for display ice-cream, frozen food and fresh pre-packed products.
TB version temperature -18/-15°C
TB/TN version temperature -18/-15°C, -1/+5°C




REFRIGERATION ARCHITECTURE



NÈSOS 150, 200, 250 TB; TB/TN



NÈSOS 150 TP



NÈSOS 200 TP



Upper in tempered glass



Internal lighting in the upper profile



Self-rolling curtain (optional)

Technical features



ISA S.p.A.
Via del Lavoro, 5
06083 BASTIA UMBRA (PG) ITALY
Tel. 075-80171 - Fax 075-8000900
<http://www.isaitaly.com>

	150 TB; TB/TN	200 TB; TB/TN	250 TB; TB/TN	150 TB TP	200 TB TP
LxPxH mm	1540x1040x959	2040x1040x959	2540x1040x959	1540x1040x959	2040x1040x959
Capacity (gross/net) litres	509/235	691/399	872/504	490/235	646/399
Product temperature °C	-18/-15; -1/+5	-18/-15; -1/+5	-18/-15; -1/+5	-18/-15	-18/-15
Voltage v/Hz	230/50	230/50	230/50	230/50	230/50
Electrical input (standard) W/A	1150/6.2	1300/6.8	1450/7.8	1280/6.8	1500/8.2
Electrical input (defrosting) W/A	1800/7.8	2450/10.2	2900/13.0	1400/8.8	1750/8.4
Defrosting	electrical	electrical	electrical	hot gas	hot gas
Net weight kg	183	214	241	183	214

Due to the quality advancement programmes and continuous scientific research ISA reserves the right to modify any technical specifications without notice.